

TECHNICAL SPECIFICATIONS OF CANVAS

Composition	Polyester knitted fabric coated with polyurethane (PU)
Fire reaction	B - s1, d0
Width	200cm / 300cm / 400cm / 515cm
Weight	245 gr/m2, +/- 10%
Thickness	0,4mm
Appearance	Matt, smooth and uniform
Colour	Matt, smooth and uniform
Strength	5 times greater than PVC film, doesn't crack CH : 5,5 daN; TR : 7,5 daN
Packaging	Cut to measure, In roll (50m)
Warranty	10 year*

*according to Dabso standard terms of sale



Anti bacterial



Anti static



UV resistant



Eco friendly



Printable



Water resistant



Light weight



Breathable



Long lasting

Thk. mm	Plenum mm	α_p Practical sound absorption coefficient						α_w	Sound absorption class
		125	250	500	1000	2000	4000		
10	200	0.30	0.85	0.95	0.85	0.95	0.90	0.95	A
20	200	0.20	0.70	0.90	0.75	0.90	0.90	0.85	B
0	155	0.15	0.35	0.65	0.60	0.55	0.60	0.60	C
50	55	0.25	0.75	1.00	1.00	0.95	0.90	1.00	A
10	10	0.15	0.25	0.50	0.70	0.90	0.95	0.50	D