


SYSTEM COMPOSITION

1. Perforated tray 160/600 th. 0,75 mm
2. Low density glasswool th. 160 mm
3. Particle board CTBH P5 th. 22mm
4. Acoustic panel PHONOTECH DK40

Absorption

$$\alpha_w = 0,95$$




α_p per octave band (Hz)

Frequency (Hz)	125	250	500	1000	2000	4000
α_p	0,75	0,90	1,00	1,00	0,95	0,75

Insulation

$$R_w (C; C_{tr}) = 54 (-5; -13) \text{ dB}$$



R (dB) per octave band (Hz)

Frequency (Hz)	63	125	250	500	1000	2000	4000
R (dB)	25,0	25,7	49,2	66,5	70,1	70,2	74,4

System	Sound reduction			α_w	Thermal R. (m ² .K/W)	U (W/m ² .K)	Weight (kg/m ²)	Thickness (mm)	PV
	R _w (dB)	RA (dB)	RA, tr (dB)						
TP160-DK40	54	49	41	0,95	6,56	0,15	47,60	254	CEDIA (03/18)

ADDRESS

Zoning Industriel les Plénesses
 Rue des Waides 8, 4890 Thimister
 Belgium

WEBSITE

www.phonotech.com
 E-MAIL
info@phonotech.com

PHONE

+32 (0) 87 33 33 30
 FAX
 +32 (0) 87 78 52 30